

“Slimline” Generator Series

OZ1BTUSL

OZ2BTUSL

Features:

- Patented “Cold Spark” corona discharge
- Air cooled operation
- High ozone concentration
- Built in air flow meters
- Safety interlock switch
- Field serviceable corona cells
- 2 year C/D cell warranty
- UL listed components, CE certified
- Wall mountable
- Powder coated aluminum chassis
- 2 year high voltage transformer warranty
- All models come standard with on/off switch
- Built-in hi temperature shut-off

Benefits:

- Extremely compact size
- High reliability
- Lightweight and corrosion resistant
- Simple and reliable operation
- Easy to service

Part #	Model #
30269	OZ1BTUSL
30269-01	OZ1BTUSL-F
30269-02	OZ1BTUSL-V/PM
30269-03	OZ1BTUSL-F/V/PM
30269-04	OZ1BTUSL-ORP
30269-05	OZ1BTUSL-F/ORP
30268	OZ2BTUSL
30268-01	OZ2BTUSL-F
30268-02	OZ2BTUSL-V/PM
30268-03	OZ2BTUSL-F/V/PM
30268-04	OZ2BTUSL-ORP
30268-05	OZ2BTUSL-F/ORP



- 220 Vac models are CE certified to applicable emissions standards

Shipping & Lead Time

Dimensions: W 9" x H 27.5" x D 10"
Shipping Weight: (OZ1BTUSL) 35 lbs
(OZ2BTUSL) 40 lbs
Max. Lead Time: 7 days

This generator series has been engineered with an economic and high quality foundation. The tried and true “cold plasma” technology has been redesigned into a smaller overall package with a handsome black powder coating for an improved appearance. Applications include bottled water, cooling towers, well water, car washers, swimming pools and textile mills.

Replacement parts are listed in the operation and maintenance manuals supplied with equipment. Ozotech, Inc. generators must be accompanied by proper air preparation or warranty will be null and void.

Model	Conc. %	Air Flow	Oxygen Flow	PP Phoenix	Onyx or OX12	G/Hr.
OZ1BTUSL	1.0	3	—	—	—	1.2
OZ1BTUSL	1.2	—	10.0	—	—	4.7
OZ1BTUSL	1.1	—	—	6	—	2.4
OZ1BTUSL	1.2	—	—	—	10	4.6
OZ2BTUSL	1.0	6	—	—	—	2.1
OZ2BTUSL	2.2	—	10.0	—	—	8.3
OZ2BTUSL	1.6	—	—	6	—	3.9
OZ2BTUSL	1.7	—	—	—	10	6.6

Concentrations up to 3.5% by weight — Deduct 18% for 50 Hz models