

PCS Generator Series

**OZ4PC10
OZ8PC20**

OZ4AW10

PART #	MODEL #
30002	OZ4PC10
30002-01	OZ4PC10-F *
30002-08	OZ4PC10-V/SW
30002-12	OZ4PC10-F/V/SW
30115	OZ4AW-SW
30115-01	OZ4AW-F/SW
30115-02	OZ4AW-SW/V
30115-03	OZ4AW-F-SW/V
30003	OZ8PC20
30003-01	OZ8PC20-F
30003-04	OZ8PC20-V/SW
30003-05	OZ8PC20-F/V/SW



Features:

- Patented “Cold Spark” corona discharge
- Safety interlock switch
- Field serviceable corona cells
- **Lifetime C/D cell warranty**
- CSA & NRTL/C approved
- Wall mountable
- Lightweight aluminum chassis
- Low power consumption

Benefits:

- Compact size
- High reliability
- Lightweight and corrosion resistant
- Simple and reliable operation
- Easy to service

* Model OZ4PC10-F is CE certified to applicable emissions standards

Shipping & Lead Time

Dimensions: PC Models W 10" x H 17.5" x D 6"
AW Models W 14" x H 16" x D 8"

Shipping Weight: 17 lbs
Max. Lead Time: 7 Days

The OZ4PC10 and OZ8PC20 balance compact size with powerful ozone output. Applications include residential water treatment, small residential pools, sanitation loops, gray water treatment and ozone pilot studies.

Replacement parts are listed in the operation and maintenance manuals supplied with equipment. Ozotech, Inc. generators should be accompanied by air preparation.

Model	Conc. %	Air Flow (SCFH)	O ² Flow (SCFH)	PP Phoenix (SCFH)	G/Hr.
OZ4PC10 & OZ4AW	.54	—	—	5	1.1
OZ4PC10 & OZ4AW	.15	10	—	—	.56
OZ8PC20	.71	—	—	5	1.5
OZ8PC20	.21	10	—	—	.76

CONCENTRATIONS UP TO 2.5% BY WEIGHT — DEDUCT 18% OUTPUT FOR 50 HZ MODELS